

STOCK PROGRAMME

PIPES & TUBES
BUTT WELD FITTINGS
FLANGES
**AUSTENITIC
STAINLESS STEEL**

STANDARD	A/SA 312 TP 304/304L, TP 316/316L	A/SA 403 WP 304/304L, WP 316/316L	A/SA 182 F 304/304L, F 316/316L	1/2" (21.3 mm)	16" (406.40 mm)
HIGH TEMPERATURE	A/SA 312 TP 321/321H, TP 304/304H	A/SA 403 WP 321/321H, WP 304/304H	ON APPLICATION	1/2" (21.3 mm)	12" (323.9 mm)
UREA GRADE	A/SA 312 TP 316L UG, 25.22.2 (UNS S31050)	A/SA 403 WP 316L UG, 25.22.2 (UNS S31050)	ON APPLICATION	1/2" (21.3 mm)	12" (323.85 mm)
HEAT EXCHANGER	A/SA 213 TP 316/316L			19.05 mm	25.4 mm
INSTRUMENTATION TUBING	A/SA 213 & 269 TP 304/304L, TP 316/316L			6 mm	25 mm

DUPLEX & SUPERDUPLEX

	A/SA 790 & 928 UNS S31803/S32205 UNS S32760 UNS S32750	A/SA 815 UNS S31803/S32205 UNS S32760 UNS S32750	A/SA 182 F 51 F 55	1/2" (21.3 mm)	16" (406.4 mm)
HEAT EXCHANGER	A/SA 789 UNS S31803/S32205			19.05 mm	25.4 mm

SUPERAUSTENITICS

	A/SA 312 UNS S31254 (6Mo)	A/SA 403 UNS S31254 (6Mo)	A/SA 182 F 44	1/2" (21.3 mm)	16" (406.4 mm)
--	-------------------------------------	-------------------------------------	-------------------------	----------------	----------------

NICKEL ALLOYS

	B/SB 444 & 423 UNS N06625, UNS N08825	B/SB 366 UNS N06625, UNS N08825	ON APPLICATION	1/2" (21.3 mm)	8" (219.1 mm)
--	--	--	-------------------	----------------	---------------

TITANIUM

	B/SB 861 & 862 TI GR 2	B/SB 363 TI GR 2	ON APPLICATION	1/2" (21.3 mm)	8" (219.1 mm)
--	--------------------------------------	----------------------------	-------------------	----------------	---------------

MANUFACTURING RANGE

GRADES

Cold Formed Butt Weld Fittings

od (min.-max.)
1/2"(21.3mm) 16" (406.4mm)
wall thickness (min.-max.)
Sch. 10S - Sch. XXS

Austenitic Stainless Steel,
Duplex, Super Duplex,
Superaustenitics (6mo),
Nickel Alloys, Titanium