

MANUFACTURES/STOCKS&SUPPLIES/PIPING MATERIALS/PIPES&TUBES/
 BUTT WELD FITTINGS/FLANGES/AUSTENITIC STAINLESS STEEL/
 DUPLEX&SUPERDUPLEX/6MO/NICKEL ALLOYS/TITANIUM



FROM STOCK

- EU & NON-EU ORIGIN
- FINISHED PRODUCT & RAW MATERIAL FOR PRODUCTION PURPOSE
- JUST IN TIME DELIVERY
- CONSTANT STOCK REPLENISHMENT GUARANTEED BY THE INTEGRATED MANUFACTURING OF BUTTWELD FITTINGS



FROM PRODUCTION

- INTEGRATED BW FITTINGS MANUFACTURING
- FOR STOCK REPLENISHMENT
- FOR ON-DEMAND PRODUCTION
- COLD FORMING



FOR PROJECTS WORLDWIDE

- COMPLETE PACKAGES
- GLOBAL NETWORK
- CUSTOMIZED SERVICE

→ PREMIUM QUALITY

ISO 9001:2015
 ISO 14001:2015
 ISO 45001:2018

NORSOK M-650 ED.4
 MAIN INTERNATIONAL STANDARDS
 NUMEROUS END-USER APPROVALS



PART OF

CTA GROUP

As part of CTA Group, Raccortubi can offer a complete supply of piping materials for your projects, in a wide variety of grades and dimensions.

STOCK PROGRAMME



PIPES & TUBES

BUTT WELD FITTINGS

FLANGES

AUSTENITIC STAINLESS STEEL

| | | | | |
|------------------------|--|--|--|--------------------------------|
| STANDARD | A/SA 312 TP 304/304L, TP 316/316L | A/SA 403 WP 304/304L, WP 316/316L | A/SA 182 F 304/304L, F 316/316L | 1/2" (21.3 mm) 16" (406.40 mm) |
| HIGH TEMPERATURE | A/SA 312 TP 321/321H, TP 304/304H | A/SA 403 WP 321/321H, WP 304/304H | ON APPLICATION | 1/2" (21.3 mm) 12" (323.9 mm) |
| UREA GRADE | A/SA 312 TP 316L UG, 25.22.2 (UNS S31050) | A/SA 403 WP 316L UG, 25.22.2 (UNS S31050) | ON APPLICATION | 1/2" (21.3 mm) 12" (323.85 mm) |
| HEAT EXCHANGER | A/SA 213 TP 316/316L | | | 19.05 mm 25.4 mm |
| INSTRUMENTATION TUBING | A/SA 213 & 269 TP 304/304L, TP 316/316L | | | 6 mm 25 mm |

DUPLEX & SUPERDUPLEX

| | | | | |
|----------------|--|--|---------------------------------|-------------------------------|
| | A/SA 790 & 928 UNS S31803/S32205 UNS S32760 UNS S32750 | A/SA 815 UNS S31803/S32205 UNS S32760 UNS S32750 | A/SA 182 F 51 F 55 | 1/2" (21.3 mm) 16" (406.4 mm) |
| HEAT EXCHANGER | A/SA 789 UNS S31803/S32205 | | | 19.05 mm 25.4 mm |

SUPERAUSTENITICS

| | | | | |
|--|-------------------------------------|-------------------------------------|-------------------------|-------------------------------|
| | A/SA 312 UNS S31254 (6Mo) | A/SA 403 UNS S31254 (6Mo) | A/SA 182 F 44 | 1/2" (21.3 mm) 16" (406.4 mm) |
|--|-------------------------------------|-------------------------------------|-------------------------|-------------------------------|

NICKEL ALLOYS

| | | | | |
|--|--|--|----------------|------------------------------|
| | B/SB 444 & 423 UNS N06625, UNS N08825 | B/SB 366 UNS N06625, UNS N08825 | ON APPLICATION | 1/2" (21.3 mm) 8" (219.1 mm) |
|--|--|--|----------------|------------------------------|

TITANIUM

| | | | | |
|--|--------------------------------------|----------------------------|----------------|------------------------------|
| | B/SB 861 & 862 TI GR 2 | B/SB 363 TI GR 2 | ON APPLICATION | 1/2" (21.3 mm) 8" (219.1 mm) |
|--|--------------------------------------|----------------------------|----------------|------------------------------|

MANUFACTURING RANGE



GRADES

Cold Formed Butt Weld Fittings

od (min.-max.)
1/2"(21.3mm) 16" (406.4mm)
wall thickness (min.-max.)
Sch. 10S - Sch. XXS

Austenitic Stainless Steel,
Duplex, Super Duplex,
Superaustenitics (6mo),
Nickel Alloys, Titanium